Low Power Consumption CMOS Circuit Design Logic Design PDF

MC74HC4060A - 14-Stage Binary Ripple Counter With Oscillator

MC74HC4060A Www.onsemi.com 2 MAXIMUM RATINGS Symbol Parameter Value Unit VCC DC Supply Voltage (Referenced To GND) â€“0.5 To +7.0 V Vin DC Input Voltage (Referenced ...

MC74HC4046A - Phase-Locked Loop - ON Semiconductor

MC74HC4046A Http://onsemi.com 3 [Phase Comparator Section] DC ELECTRICAL CHARACTERISTICS (Voltages Referenced To GND) Symbol Parameter Test Conditions

Application Circuit Examples - Hamamatsu Photonics

Si Photodiodes 42 Extracting The Photodiode Signal From The Cathode Terminal Is Another Effective Means. An Effective Countermeasure Against AC Noise From The Power ...

Regulating Pulse Width Modulator Datasheet - TI.com

BLOCK DIAGRAM UC1526A UC2526A UC3526A Regulating Pulse Width Modulator FEATURES â€¢ Reduced Supply Current â€¢ Oscillator Frequency To 600kHz â€¢ Precision Band-Gap ...

CD54HC32, CD74HC32, CD54HCT32, CD74HCT32 (Rev. C)

2 Functional Diagram HC Logic Symbol HCT Logic Symbol TRUTH TABLE INPUTS OUTPUT NA NB NY LL L LH H HL H HH H H = High Voltage Level, L = Low Voltage Level

This Product Is Not Recommended For ... - Power Integrations

Figure 1. Typical Flyback Application. Reduces Cost In Lower Power, High Efficiency Applications. The Internal Lead Frame Of This Package Uses Six Of Its Pins To

HT77XX -- PFM Step-up DC/DC Converter

HT77XX PFM Step-up DC/DC Converter Selection Table Part No. Output Voltage Package Marking HT7718 1.8V TO92 SOT89 SOT23 SOT23-5 HT77XX (for TO92) HT77XX# (for SOT89)

Previous Page - Tuks

Ã°b ZÃž Mn Â¼ J ï¬ƒï¬ƒï¬ƒ